
Item no.:	222-415
Product description:	COMPACT CONNECTOR 5-CONDUCTOR TERMINAL BLOCK WITH LEVERS MAX. CONTINUOUS USAGE TEMPERATURE 85 °C



Packing unit 400 10*40 pieces

Product group	7 (Push Wire Conn.)
Cross section [mm ²]	0.08 - 2.5 mm ²
Cross section [AWG]	28 - 14 AWG
Wiring method	e+f
Connection method	CAGE CLAMP® CONNECTION
Cross section [mm ²]	0.08 - 4 mm ²
Cross section [AWG]	28 - 12 AWG
Wiring method	f
Measured voltage EN	400 V
Measured shock voltage	4 kV
Pollution degree	2
Current intensity EN	32 A
Measured voltage EN	600 V
Current intensity EN	20 A

Weight	6.6 g
Color	gray
Wiring type	Side-entry
No. of connection Points	5
No. of potentials	1
Height	14.5 mm
Height	0.571 in
Width	26.6 mm
Width	1.047 in
Depth	20.5 mm
Depth	0.807 in
Strip length from	9 mm
Strip length to	10 mm
Strip length	0.37 in
Customs Tariff No.	85369010
Country of Origin	Deutschland

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected