



Constant Voltage LED Power Supply 24V IP67 200W



## FEATURES:

- Universal input voltage range
- Protection: Short circuit / Over load / Over temperature
- Cooling by free air convection
- Tested under full load
- Built-in active power factor correction PFC
- IP67 may be used for internal and external applications

| MODEL                          |   | MCHQ200V24  |
|--------------------------------|---|---|
| OUTPUT                         | Rated voltage   | 24V   |
|                                | Rated current   | 8,33A   |
|                                | Current range   | 0 ÷ 8,33A   |
|                                | Rated power   | 200W  |
|                                | Ripple & noise (typ.)   | 600mV <sub>P-P</sub>                                  |
|                                | Voltage tolerance   | ±5%   |
| INPUT                          | Voltage range   | 90 ÷ 264VAC   |
|                                | Frequency range   | 47 ÷ 63Hz   |
|                                | PFC   | >0.95 / 230VAC full load                              |
|                                | Efficiency (typ.)   | 90%   |
|                                | AC current (typ.)   | 1.44A / 230VAC  |
|                                | Inrush current (max.)   | 75A / 230VAC (cold start)                             |
|                                | Leakage current   | 1mA/230VAC  |
| PROTECTIONS                    | Short circuit   | Type: hiccup mode, auto-recovery                      |
|                                | Over load   | Range: 110 ÷ 160 % of the nominal                     |
|                                |   | Auto-recovery.  |
|                                | Over voltage  | Range: the voltage at the output terminals 14 ÷ 20VDC |
|                                |   | Type: hiccup mode, auto-recovery                      |
|                                | Over temperature  | Detection of the main control circuit                 |
|                                |   | Type: hiccup mode, auto-recovery                      |
| ENVIRONMENT                    | Working temperature   | -20°C ÷ +45°C   |
|                                | Working humidity  | 20 ÷ 90% RH (non-condensing)                          |
|                                | Storage temperature and humidity  | -30°C ÷ +70°C; 10 ÷ 95% RH (non-condensing)           |
| SAFETY<br>REGULATIONS &<br>EMC | Safety standards  | EN61347-1, EN61347-2-13                               |
|                                | Withstand voltage   | I-O: 3.75kVAC; I-P: 3.75kVAC; O-P: 1.88kVAC           |
|                                | Emission - EMI  | EN55015, EN61000-3-2, EN61000-3-3                     |
|                                | Immunity - EMI  | EN61547   |
| OTHERS                         | Dimensions  | 237*67*42mm   |
|                                | Weight  | 1.3kg   |
|                                | <ol> <li>All parametrs NOT specially mentioned are measured at 230VAC input rated load and 25°C temperature.</li> <li>Tolerance expresses the maximum range of the output voltage by switching taking into account changes depending on the input voltage and changes according to changes in load current.</li> <li>The power supply is according to the standard EN61204 component designed for installation in the final product by qualified personnel and should not be treated as a stand-alone device. The final effect of electromagnetic compatibility is determined for the final product, the declaration of conformity is required for all installation.</li> </ol> |   |

## ELECTRICAL SPECIFICATION





## **MECHANICAL SPECIFICATION**

